

Trac with FastCGI

?FastCGI interface allows Trac to remain resident much like with mod_python. It is faster than external CGI interfaces which must start a new process for each request. However, unlike mod_python, FastCGI supports ?Apache SuEXEC, i.e. run with different permissions than web server. Additionally, it is supported by much wider variety of web servers.

Note for Windows: Trac's FastCGI does not run under Windows, as Windows does not implement `Socket.fromfd`, which is used by `_fcgi.py`. If you want to connect to IIS, you may want to try ?AJP.

Simple Apache configuration

There are two FastCGI modules commonly available for Apache: `mod_fastcgi` and `mod_fcgid` (preferred). The latter is more up-to-date.

setup with `mod_fastcgi`

`mod_fastcgi` uses `FastCgiIpcDir` and `FastCgiConfig` directives that should be added to an appropriate Apache configuration file:

```
# Enable fastcgi for .fcgi files
# (If you're using a distro package for mod_fcgi, something like
# this is probably already present)
<IfModule mod_fastcgi.c>
    AddHandler fastcgi-script .fcgi
    FastCgiIpcDir /var/lib/apache2/fastcgi
</IfModule>
LoadModule fastcgi_module /usr/lib/apache2/modules/mod_fastcgi.so
```

Setting `FastCgiIpcDir` is optional if the default is suitable. Note that the `LoadModule` line must be after the `IfModule` group.

Configure `ScriptAlias` or similar options as described in TracCgi, but calling `trac.fcgi` instead of `trac.cgi`.

You can set up the `TRAC_ENV` as an overall default:

```
FastCgiConfig -initial-env TRAC_ENV=/path/to/env/trac
```

Or you can serve multiple Trac projects in a directory like:

```
FastCgiConfig -initial-env TRAC_ENV_PARENT_DIR=/parent/dir/of/projects
```

setup with `mod_fcgid`

Configure `ScriptAlias` (see [TracCgi](#) for details), but call `trac.fcgi` instead of `trac.cgi`. Note that slash at the end - it is important.

```
ScriptAlias /trac /path/to/www/trac/cgi-bin/trac.fcgi/
```

To setup Trac environment for `mod_fcgid` it is necessary to use `DefaultInitEnv` directive. It cannot be used in `Directory` or `Location` context, so if you need to support multiple projects, try alternative environment setup below.

```
DefaultInitEnv TRAC_ENV /path/to/env/trac/
```

alternative environment setup

A better method to specify path to Trac environment is to embed the path into `trac.fcgi` script itself. That doesn't require configuration of server environment variables, works for both FastCgi? modules (and for [?lighttpd](#) and CGI as well):

```
import os
os.environ['TRAC_ENV'] = "/path/to/projectenv"
```

or

```
import os
os.environ['TRAC_ENV_PARENT_DIR'] = "/path/to/project/parent/dir"
```

With this method different projects can be supported by using different `.fcgi` scripts with different `ScriptAliases`.

See [?this fcgid example config](#) which uses a `ScriptAlias` directive with `trac.fcgi` with a trailing `/` like this:

```
ScriptAlias / /srv/tracsite/cgi-bin/trac.fcgi/
```

Simple Cherokee Configuration

The configuration on Cherokee's side is quite simple. You will only need to know that you can spawn Trac as an SCGI process. You can either start it manually, or better yet, automatically by letting Cherokee spawn the server whenever it is down. First set up an information source in cherokee-admin with a local interpreter.

```
Host:
```

```
localhost:4433
```

```
Interpreter:
```

```
/usr/bin/tracd ?single-env ?daemonize ?protocol=scgi ?hostname=localhost ?port=4433 /path/to/p
```

If the port was not reachable, the interpreter command would be launched. Note that, in the definition of the information source, you will have to manually launch the spawner if you use a *Remote host* as *Information source* instead of a *Local interpreter*.

After doing this, we will just have to create a new rule managed by the SCGI handler to access Trac. It can be created in a new virtual server, trac.example.net for instance, and will only need two rules. The **default** one will use the SCGI handler associated to the previously created information source. The second rule will be there to serve the few static files needed to correctly display the Trac interface. Create it as *Directory rule* for */chrome/common* and just set it to the *Static files* handler and with a *Document root* that points to the appropriate files:

```
/usr/share/trac/htdocs/
```

Simple Lighttpd Configuration

The FastCGI front-end was developed primarily for use with alternative web servers, such as [lighttpd](#).

lighttpd is a secure, fast, compliant and very flexible web-server that has been optimized for high-performance environments. It has a very low memory footprint compared to other web servers and takes care of CPU load.

For using `trac.fcgi` (prior to 0.11) / `fcgi_frontend.py` (0.11) with lighttpd add the following to your `lighttpd.conf`:

```
#var.fcgi_binary="/usr/bin/python /path/to/fcgi_frontend.py" # 0.11 if installed with easy_set
var.fcgi_binary="/path/to/cgi-bin/trac.fcgi" # 0.10 name of prior fcgi executable
fastcgi.server = ("/trac" =>

    ("trac" =>
        ("socket" => "/tmp/trac-fastcgi.sock",
         "bin-path" => fcgi_binary,
         "check-local" => "disable",
         "bin-environment" =>
             ("TRAC_ENV" => "/path/to/projenv")
        )
    )
)
```

Note that you will need to add a new entry to `fastcgi.server` for each separate Trac instance that you wish to run. Alternatively, you may use the `TRAC_ENV_PARENT_DIR` variable instead of `TRAC_ENV` as described above, and you may set one of the two in `trac.fcgi` instead of in `lighttpd.conf` using `bin-environment` (as in the section

above on Apache configuration).

Note that lighttpd has a bug related to 'SCRIPT_NAME' and 'PATH_INFO' when the uri of fastcgi.server is '/' instead of '/trac' in this example, see #Trac2418. This should be fixed since lighttpd 1.4.23, and you may need to add "fix-root-scriptname" => "enable" as parameter of fastcgi.server.

For using two projects with lighttpd add the following to your lighttpd.conf:

```
fastcgi.server = (("/first" =>
    ("first" =>
        ("socket" => "/tmp/trac-fastcgi-first.sock",
        "bin-path" => fcgi_binary,
        "check-local" => "disable",
        "bin-environment" =>
            ("TRAC_ENV" => "/path/to/projenv-first")
        )
    ),
    "/second" =>
        ("second" =>
            ("socket" => "/tmp/trac-fastcgi-second.sock",
            "bin-path" => fcgi_binary,
            "check-local" => "disable",
            "bin-environment" =>
                ("TRAC_ENV" => "/path/to/projenv-second")
            )
        )
    )
)
```

Note that field values are different. If you prefer setting the environment variables in the .fcgi scripts, then copy/rename trac.fcgi, e.g., to first.fcgi and second.fcgi, and reference them in the above settings. Note that the above will result in different processes in any event, even if both are running from the same trac.fcgi script.

Note It's very important the order on which server.modules are loaded, if mod_auth is not loaded **BEFORE** mod_fastcgi, then the server will fail to authenticate the user.

For authentication you should enable mod_auth in lighttpd.conf 'server.modules', select auth.backend and auth rules:

```
server.modules = (
    ...
    "mod_auth",
    ...
)
```

```

auth.backend                                = "htpasswd"

# Separated password files for each project
# See "Conditional Configuration" in
# http://trac.lighttpd.net/trac/file/branches/lighttpd-merge-1.4.x/doc/configuration.txt

$HTTP["url"] =~ "^/first/" {
    auth.backend.htpasswd.userfile = "/path/to/projenv-first/htpasswd.htaccess"
}
$HTTP["url"] =~ "^/second/" {
    auth.backend.htpasswd.userfile = "/path/to/projenv-second/htpasswd.htaccess"
}

# Enable auth on trac URLs, see
# http://trac.lighttpd.net/trac/file/branches/lighttpd-merge-1.4.x/doc/authentication.txt

auth.require = ("/first/login" =>
    ("method"  => "basic",
     "realm"   => "First project",
     "require" => "valid-user"
    ),
    "/second/login" =>
    ("method"  => "basic",
     "realm"   => "Second project",
     "require" => "valid-user"
    )
)

```

Note that lighttpd (I use version 1.4.3) stopped if password file doesn't exist.

Note that lighttpd doesn't support 'valid-user' in versions prior to 1.3.16.

Conditional configuration is also useful for mapping static resources, i.e. serving out images and CSS directly instead of through FastCGI:

```

# Aliasing functionality is needed
server.modules += ("mod_alias")

# Setup an alias for the static resources
alias.url = ("/trac/chrome/common" => "/usr/share/trac/htdocs")

# Use negative lookahead, matching all requests that ask for any resource under /trac, EXCEPT
# /trac/chrome/common, and use FastCGI for those
$HTTP["url"] =~ "^/trac(?!/chrome/common)" {

```

```
# Even if you have other fastcgi.server declarations for applications other than Trac, do NOT
fastcgi.server = ("/trac" =>
    ("trac" =>
        ("socket" => "/tmp/trac-fastcgi.sock",
            "bin-path" => fcgi_binary,
            "check-local" => "disable",
            "bin-environment" =>
                ("TRAC_ENV" => "/path/to/projenv")
            )
        )
    )
)
```

The technique can be easily adapted for use with multiple projects by creating aliases for each of them, and wrapping the fastcgi.server declarations inside conditional configuration blocks. Also there is another way to handle multiple projects and it's to use TRAC_ENV_PARENT_DIR instead of TRAC_ENV and use global auth, let's see an example:

```
# This is for handling multiple projects
alias.url      = ( "/trac/" => "/path/to/trac/htdocs/" )

fastcgi.server += ("/projects" =>
    ("trac" =>
        (
            "socket" => "/tmp/trac.sock",
            "bin-path" => fcgi_binary,
            "check-local" => "disable",
            "bin-environment" =>
                ("TRAC_ENV_PARENT_DIR" => "/path/to/parent/dir/of/projects/" )
            )
        )
    )

#And here starts the global auth configuration
auth.backend = "htpasswd"
auth.backend.htpasswd.userfile = "/path/to/unique/htpasswd/file/trac.htpasswd"
$HTTP["url"] =~ "^/projects/./login$" {
    auth.require = ("/" =>
        (
            "method" => "basic",
            "realm" => "trac",
            "require" => "valid-user"
        )
    )
}
```

Changing date/time format also supported by lighttpd over environment variable LC_TIME

```

fastcgi.server = ("/trac" =>
    ("trac" =>
        ("socket" => "/tmp/trac-fastcgi.sock",
            "bin-path" => fcgi_binary,
            "check-local" => "disable",
            "bin-environment" =>
                ("TRAC_ENV" => "/path/to/projenv",
                    "LC_TIME" => "ru_RU")
            )
        )
    )
)

```

For details about languages specification see [?TracFaq](#) question 2.13.

Other important information like [?this updated TracInstall page](#), [and this](#) are useful for non-fastcgi specific installation aspects.

If you use trac-0.9, read [?about small bug](#)

Relaunch lighttpd, and browse to `http://yourhost.example.org/trac` to access Trac.

Note about running lighttpd with reduced permissions:

If nothing else helps and trac.fcgi doesn't start with lighttpd settings `server.username = "www-data"`, `server.groupname = "www-data"`, then in the `bin-environment` section set `PYTHON_EGG_CACHE` to the home directory of `www-data` or some other directory accessible to this account for writing.

Simple LiteSpeed Configuration

The FastCGI front-end was developed primarily for use with alternative web servers, such as [?LiteSpeed](#).

LiteSpeed web server is an event-driven asynchronous Apache replacement designed from the ground-up to be secure, scalable, and operate with minimal resources. LiteSpeed can operate directly from an Apache config file and is targeted for business-critical environments.

Setup

1. Please make sure you have first have a working install of a Trac project. Test install with `?tracd?` first.

2. Create a Virtual Host for this setup. From now on we will refer to this vhost as TracVhost. For this tutorial we will be assuming that your trac project will be accessible via:

```
http://yourdomain.com/trac/
```

3. Go to TracVhost External Apps tab and create a new External Application.

```
Name: MyTracFCGI
Address: uds://tmp/lshttpd/mytracfcgi.sock
Max Connections: 10
Environment: TRAC_ENV=/fullpath/to/mytracproject/ <--- path to root folder of trac project
Initial Request Timeout (secs): 30
Retry Timeout (secs): 0
Persistent Connection Yes
Connection Keepalive Timeout: 30
Response Bufferring: No
Auto Start: Yes
Command: /usr/share/trac/cgi-bin/trac.fcgi <--- path to trac.fcgi
Back Log: 50
Instances: 10
```

4. Optional. If you need to use htpasswd based authentication. Go to TracVhost Security tab and create a new security Realm.

```
DB Type: Password File
Realm Name: MyTracUserDB <--- any name you wish and referenced later
User DB Location: /fullpath/to/htpasswd <--- path to your htpasswd file
```

If you don't have a htpasswd file or don't know how to create the entries within one, go to <http://sherylcanter.com/encrypt.php>, to generate the user:password combos.

5. Go to PythonVhost Contexts and create a new FCGI Context.

```
URI: /trac/ <--- URI path to bind to python fcgi app we created
Fast CGI App: [VHost Level] MyTracFCGI <--- select the trac fcgi extapp we just created
Realm: TracUserDB <--- only if (4) is set. select realm created in (4)
```

6. Modify /fullpath/to/mytracproject/conf/trac.ini

```
#find/set base_url, url, and link variables
base_url = http://yourdomain.com/trac/ <--- base url to generate correct links to
url = http://yourdomain.com/trac/ <--- link of project
link = http://yourdomain.com/trac/ <--- link of graphic logo
```


7. Restart LiteSpeed, `?lsctl restart?`, and access your new Trac project at:

`http://yourdomain.com/trac/`

Simple Nginx Configuration

1. Nginx configuration snippet - confirmed to work on 0.6.32

```
server {
    listen      10.9.8.7:443;
    server_name trac.example;

    ssl          on;
    ssl_certificate      /etc/ssl/trac.example.crt;
    ssl_certificate_key  /etc/ssl/trac.example.key;

    ssl_session_timeout 5m;

    ssl_protocols  SSLv2 SSLv3 TLSv1;
    ssl_ciphers    ALL:!ADH:!EXPORT56:RC4+RSA:+HIGH:+MEDIUM:+LOW:+SSLv2:+EXP;
    ssl_prefer_server_ciphers  on;

    # (Or ``^/some/prefix/(.*)``.
    if ($uri ~ ^/(.*)) {
        set $path_info /$1;
    }

    # You can copy this whole location to ``location [/some/prefix]/login``
    # and remove the auth entries below if you want Trac to enforce
    # authorization where appropriate instead of needing to authenticate
    # for accessing the whole site.
    # (Or ``location /some/prefix``.)
    location / {
        auth_basic          "trac realm";
        auth_basic_user_file /home/trac/htpasswd;

        # socket address
        fastcgi_pass        unix:/home/trac/run/instance.sock;

        # python - wsgi specific
        fastcgi_param        HTTPS on;

        ## WSGI REQUIRED VARIABLES
        # WSGI application name - trac instance prefix.
        # (Or ``fastcgi_param SCRIPT_NAME /some/prefix``.)
        fastcgi_param        SCRIPT_NAME        "";
```

```

        fastcgi_param  PATH_INFO            $path_info;

        ## WSGI NEEDED VARIABLES - trac warns about them
        fastcgi_param  REQUEST_METHOD      $request_method;
        fastcgi_param  SERVER_NAME         $server_name;
        fastcgi_param  SERVER_PORT         $server_port;
        fastcgi_param  SERVER_PROTOCOL     $server_protocol;
        fastcgi_param  QUERY_STRING        $query_string;

        # for authentication to work
        fastcgi_param  AUTH_USER            $remote_user;
        fastcgi_param  REMOTE_USER          $remote_user;
    }
}

```

2. Modified trac.fcgi:

```

#!/usr/bin/env python
import os
sockaddr = '/home/trac/run/instance.sock'
os.environ['TRAC_ENV'] = '/home/trac/instance'

try:
    from trac.web.main import dispatch_request
    import trac.web._fcgi

    fcgiserv = trac.web._fcgi.WSGIServer(dispatch_request,
        bindAddress = sockaddr, umask = 7)
    fcgiserv.run()

except SystemExit:
    raise
except Exception, e:
    print 'Content-Type: text/plain\r\n\r\n',
    print 'Oops...'
    print
    print 'Trac detected an internal error:'
    print
    print e
    print
    import traceback
    import StringIO
    tb = StringIO.StringIO()
    traceback.print_exc(file=tb)
    print tb.getvalue()

```

3. reload nginx and launch trac.fcgi like that:

```
trac@trac.example ~ $ ./trac-standalone-fcgi.py
```

The above assumes that:

- There is a user named 'trac' for running trac instances and keeping trac environments in its home directory.
- `/home/trac/instance` contains a trac environment
- `/home/trac/htpasswd` contains authentication information
- `/home/trac/run` is owned by the same group the nginx runs under
 - ◆ and if your system is Linux the `/home/trac/run` has setgid bit set (`chmod g+s run`)
 - ◆ and patch from ticket #T7239 is applied, or you'll have to fix the socket file permissions every time

Unfortunately nginx does not support variable expansion in `fastcgi_pass` directive. Thus it is not possible to serve multiple trac instances from one server block.

If you worry enough about security, run trac instances under separate users.

Another way to run trac as a FCGI external application is offered in ticket #T6224

See also: [TracGuide](#), [TracInstall](#), [ModWSGI](#), [CGI](#), [ModPython](#), [?TracNginxRecipe](#)